

Composite Distribution Amplifier

NEW!

**1x4
Composite DA**

4910 Composite Distribution Amplifier

The Solution for multiple composite inputs!

Features include:

Ten Turn Sealed Pots for level adjust

Independent Level adjust for each channel.



Composite DA

Part Number 4910-000 \$499.00

Rack Mount Kit for W line products

Part Number 4900-010 \$89

Product Specifications

Physical Size

5.7 (w) x 6.0 (d) x 1.6 (h) inches

Operating Environment

Extended Indoor Environment

0 to +50 degrees C.

0 to 95% R.H. (Non-Condensing)

Power Input: 24Vdc @ 200 mA max.

115Vac wall transformer supplied

Maximum Input Level: 10 V p-p

Input Impedance: 2k

Output Level: Adjustable from 0 to 5 Vp-p

Output Impedance: 75 ohms

Frequency response: 0 to 100kHz +/- 0.1 dB

Noise Floor: Better than -80 dB

THD: less than 0.1%

Maximum gain: 10 dB

Output Isolation: greater than 40 dB

Input Connector Type: BNC

Output Connector Type: BNC

**Available from your favorite distributor of
fine broadcast equipment.**

MTS COMMUNICATION
PRODUCTS DIV.

150 Clayton Commerce Center

Clayton, NC 27520

(919) 553-2995 Voice

(919) 553-0437 Fax

www.mts-comm.com